



Flaming River Industries, Inc.
 800 Poertner Drive Berea, OH 44017
 1-800-648-8022 | www.flamingriver.com

Combination Battery and Alternator Kill Switch Product Specifications Sheet

	
Description	Combination Battery and Alternator Kill Switch
Part No.	FR1013
Warranty	3 Years
Voltage	12V/24V
Max Continuous Current	150 Amps (battery)
Max Surge Current	1,200 Amps (5 seconds)
Max Current for Auxiliary Terminals	5 Amps
Environmental Protection Rating	IP65
Alternator	120 Amps
Waterproof	Yes
Operating Temperature Range	-30°C to +60°C -22°F to +140°F
Contact Terminals	Silver Plated Copper
Contact Hardware	Brass
Stud Diameter	M10
Available Stud Length	0.813" (approx. 13/16 in)
Max Tightening Torque	11-13 ft·lbs
LED ON/OFF Indicator	No
Lock-Out Capability	No
Mounting Bracket Included	No
Protective Cover Included	No
Extension Handle/Lever	No
Additional Notes	Approved for IHRA, NHRA, and SCCA competition use

WARNING: Flaming River Industries, Inc. make no recommendation as to mounting location or product suitability to your vehicle application. For each kit, contact your vehicle's manufacturer to determine proper placement and suitability. When installed, a battery disconnect switch is a functioning and live part of the electrical current system and should be treated like battery terminals.