




Flaming River Industries, Inc.
800 Poertner Drive Berea, OH 44017
1-800-648-8022 | www.flamingriver.com

Dual Battery Disconnect Switch Product Specifications Sheet

	
Description	Dual Battery Disconnect Switch
Part No.	FR1050
Warranty	3 Years
Voltage	12V and 24V
Max Continuous Current	300 Amps
Max Surge Current	1,000 Amps (5 seconds)
Environmental Protection Rating	IP54
Operating Temperature Range	-40°C to +50°C -40°F to +122°F
Internal Contacts:	Silver Plated Copper
Contact Terminals	Copper
Contact Hardware	Brass
Stud Diameter	M10
Available Stud Length	0.5" (1/2 in)
Tightening Torque	11-13 ft·lbs
Switch Modes	4 Modes: #1 On, #2 On, Both On, Both Off
LED ON/OFF Indicator	No
Lock-Out Capability	No
Mounting Bracket Included	No
Protective Cover Included	No
Extension Handle/Lever	No

WARNING: Flaming River Industries, Inc. make no recommendation as to mounting location or product suitability to your vehicle application. For each kit, contact your vehicle's manufacturer to determine proper placement and suitability. When installed, a battery disconnect switch is a functioning and live part of the electrical current system and should be treated like battery terminals.