

800 Poertner Dr. Berea, OH 44017 1-800-648-8022 | flamingriver.com

Mustang II Style Power Rack and Pinion Specifications Sheet




	Mustang II Power Rack	Mustang II Power Rack	Mustang II Power Rack	- Mustang II Power Rack -
	Cast Housing (Blue)	Cast Housing (Plain)	Billet Housing (Blue)	Billet Housing (Plain)
Part No.	FR40001	FR40001PLN	FR40001-B	FR40001PLN-B
OEM Design Style	74-78 Ford Mustang	74-78 Ford Mustang	74-78 Ford Mustang	74-78 Ford Mustang
Steering Design	Front Steer	Front Steer	Front Steer	Front Steer
Total Weight	20 lbs	20 lbs	20 lbs	20 lbs
Housing Material	Die Cast Aluminum	Die Cast Aluminum	Billet Aluminum	Billet Aluminum
Tube Material	1026 Dom Steel Tubing			
Tube Plating	Powder Coat	Powder Coat	Powder Coat	Powder Coat
Rack Gain	2.27" Per Revolution	2.27" Per Revolution	2.27" Per Revolution	2.27" Per Revolution
No. Turns Lock-to-Lock	2.7	2.7	2.7	2.7
Total Rack Travel	6.00"	6.00"	6.00"	6.00"
Overall Length (end to end)	45"	45"	45"	45"
Body Length (Tube/Casting)	19.5"	19.5"	19.5"	19.5"
Housing O.D.	2.15" (1.98" at bellow			
	clamp)	clamp)	clamp)	clamp)
Tube O.D. (passenger side)	2.02"	2.02"	2.02"	2.02"
Input Shaft Angle	18°	18°	18°	18°
Input Shaft Spline Size	FR Pyramid	FR Pyramid	FR Pyramid	FR Pyramid
Input Shaft Length	2.5"-2.63" from top of			
	valve housing	valve housing	valve housing	valve housing
Pivot Points	24.25"	24.25"	24.25"	24.25"
Inner End Diameter	.551"	.551"	.551"	.551"
Inner End Thread Size	9/16"-18	9/16"-18	9/16"-18	9/16"-18
Driver Side Mount	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)
Passenger Side Mount	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)
Spike Mount Center to	16.00"	16.00"	16.00"	16.00"
Center Distance				
Bellows Material	TPV	TPV	TPV	TPV
Bellows Part No.	100163	100163	100163	100163
Bushing Part No.	FR1600 (2 req'd)	FR1600 (2 req'd)	FR1600 (2 req'd)	FR1600 (2 req'd)
Outer End Part No.	FR1601 (2 req'd)	FR1601 (2 req'd)	FR1601 (2 req'd)	FR1601 (2 req'd)



1-800-648-8022 | flamingriver.com

Mustang Style Power Rack & Pinion (with 15.5" Mounts) Specifications Sheet







	Mustang Style Power	Mustang Style Power	Mustang Style Power	Mustang Style Power
	Rack - Cast Housing	Rack - Cast Housing	Rack - Billet Housing	Rack - Billet Housing
	(Blue)	(Plain)	(Blue)	(Plain)
Part No.	FR40002	FR40002PLN	FR40002-B	FR40002PLN-B
OEM Design Style	Ford Mustang Style with			
	15.5" mounts	15.5" mounts	15.5" mounts	15.5" mounts
Steering Design	Front Steer	Front Steer	Front Steer	Front Steer
Total Weight	20 lbs	20 lbs	20 lbs	20 lbs
Housing Material	Die Cast Aluminum	Die Cast Aluminum	Billet Aluminum	Billet Aluminum
Tube Material	1026 Dom Steel Tubing			
Tube Plating	Powder Coat	Powder Coat	Powder Coat	Powder Coat
Rack Gain	2.27" Per Revolution	2.27" Per Revolution	2.27" Per Revolution	2.27" Per Revolution
No. Turns Lock-to-Lock	2.7	2.7	2.7	2.7
Total Rack Travel	6.00"	6.00"	6.00"	6.00"
Overall Length (end to end)	45"	45"	45"	45"
Body Length (Tube/Casting)	19.5"	19.5"	19.5"	19.5"
Housing O.D.	2.15" (1.98" at bellow			
_	clamp)	clamp)	clamp)	clamp)
Tube O.D. (passenger side)	2.02" (after	2.02" (after	2.02" (after	2.02" (after
	powdercoating)	powdercoating)	powdercoating)	powdercoating)
Input Shaft Angle	18°	18°	18°	18°
Input Shaft Spline Size	FR Pyramid	FR Pyramid	FR Pyramid	FR Pyramid
Input Shaft Length	2.5"-2.63" from top of			
	valve housing	valve housing	valve housing	valve housing
Pivot Points	24.25"	24.25"	24.25"	24.25"
Inner End Diameter	.551"	.551"	.551"	.551"
Inner End Thread Size	9/16"-18	9/16"-18	9/16"-18	9/16"-18
Driver Side Mount	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)
Passenger Side Mount	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)	Spike (bushing req'd)
Spike Mount Center to Center	15.50"	15.50"	15.50"	15.50"
Distance				
Bellows Material	TPV	TPV	TPV	TPV
Bellows Part No.	100163	100163	100163	100163
Bushing Part No.	FR1600 (2 req'd)	FR1600 (2 req'd)	FR1600 (2 req'd)	FR1600 (2 req'd)
Outer End Part No.	FR1601 (2 req'd)	FR1601 (2 req'd)	FR1601 (2 req'd)	FR1601 (2 req'd)