



800 Poertner Dr. Berea, OH 44017
 1-800-648-8022 | flamingriver.com

Flaming River Universal Joints Specs Sheet



	Billet-Joint®	Double Billet-Joint®	Stainless	Double Stainless	Chrome-Moly	Double Chrome-Moly	Forged True®	Pinch Bolt
Material	Nickel-Plated	Nickel-Plated	303 Stainless Steel	303 Stainless Steel	Chrome-Moly	Chrome-Moly	Steel	304 Stainless Steel
Finish	Satin or Polished	Satin or Polished	Satin or Polished	Satin or Polished	Black Oxide	Black Oxide	Black Oxide	Satin or Polished
Design	Needle Bearing	Needle Bearing	Needle Bearing	Needle Bearing	Needle Bearing	Needle Bearing	Needle Bearing	Pinch Bolt
Overall Length	3.25"	5.125"	3.25"	5.125"	3.75"	5.7"	3.75"	3.25"
Max Diameter	1.5"	1.5"	1.5"	1.5"	1.25"	1.375"	1.25"	1.5"
Max Angle	Up to 30°	Up to 60°	Up to 30°	Up to 60°	Up to 35°	Up to 80°	Up to 40°	Up to 30°
Low Profile	No	No	No	No	Yes	Yes	Yes	No
Application	Street	Street	Street	Street	Street / Racing	Street / Racing	Racing	Street
Weldable	No	No	No	No	Yes	Yes	Yes	No